



LISTING INFORMATION OF
Global Innovations LLC - Endureed
SPEC ID: 49042

Global Innovation, LLC
313 SW Windswept Glen
Lake City, FL 32024
United States

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

LISTING INFORMATION

PRODUCT COVERED

Endureed® Regions Thatch Roofing Shingles

PRODUCT DESCRIPTION

Endureed® Regions Thatch Roofing Shingles are mechanically attached thatch roofing singles comprised of FR PVC extruded rods.

RATINGS

FIRE ROOF CLASSIFICATION - ASTM E108 CLASS A

Assembly No.	Endureed® Regions Thatch Roofing Shingles
Slope	5:12 or greater
Deck Type	Combustible
Details	• Minimum nominal thick AC plywood • A single layer of 1/2" DensDeck mechanically fastened to the plywood sheathing every 12" o.c. in the field • A single layer of Soprema FR Plus self-adhered • Endureed Regions Thatch Roofing Shingles mechanically fastened with a 6-1/2" reveal installed per manufacturer's installation instructions

Attribute	Value
Criteria	ASTM E108 (2017)
CSI Code	07 31 00 Shingles and Shakes
Intertek Services	Certification
Listed or Inspected	LISTED
Listing Section	ROOFING MATERIALS
Spec ID	49042